

US005971751A

## United States Patent [19]

Lee [45] Date of Pa

[11] Patent Number: 5,971,751 [45] Date of Patent: Oct. 26, 1999

[54]		SAFETY APPARATUS OF A PIEZOELECTRIC LIGHTER						
[75]	Inventor	:: Thor	mas Ping Hua Lee, Industry, Calif.					
[73]	Assigne	e: Chu	n Ching Yeh, Covina, Calif.					
[21]	Appl. N	Appl. No.: 08/881,964						
[22]	Filed:	Jun.	5, 1997					
[52]	U.S. Cl. Field of	Search	F23Q 7/12; F23D 11/36 431/255; 431/153; 431/256 431/274, 277, 153, 256, 276; 222/153.13, 402.11, 406, 113					
[56]		Re	eferences Cited					
U.S. PATENT DOCUMENTS								
	3,826,952	7/1974	Schlamp       431/255         Iwasaki et al.       431/255         Mohr       431/255					

3,733,313	2/17/0	осшанр	TJ1/455
3,826,952	7/1974	Iwasaki et al	431/255
3,984,738	10/1976	Mohr	431/255
4,471,404	9/1984	Nitta	431/255
4,786,248	11/1988	Nitta	431/255
4,810,187	3/1989	Nítta	431/255
4,859,172	8/1989	Nitta	431/255
4,859,174	8/1989	Zellweger et al	431/255
5,104,313	4/1992	Zellweger	431/277
5,120,215	6/1992	Nollas	431/153
5,178,532	1/1993	Frigiere	431/255

3/1993 Yang ...... 431/153

7/1993 Frigiere ...... 431/255

8/1993 Kenjiro et al. ...... 431/153

8/1994 Frigiere ...... 431/153

5,197,870

5,228,849 5,240,408

5,350,294 5,368,473 5,427,522 5,460,520 5,462,432 5,472,338 5,558,514 5,584,682 5,704,776	11/1994 6/1995 10/1995 10/1995 12/1995 9/1996 12/1996	Iwahori         Kenjiro et al.         McDonough et al.         Lin         Kim         Ansquer         McDonough et al.         Sher	431/153 431/153 431/255 431/153 431/153 431/153
---	---	---	--

Primary Examiner—Ira S. Lazarus Assistant Examiner—David Lee Attorney, Agent, or Firm—David and Raymond; Raymond Y. Chan

## [57] ABSTRACT

A safety apparatus of a piezoelectric lighter includes a pressure absorbing device disposed in a cap cavity of a casing of the piezoelectric lighter, a holding means integrally affixed to an interior surface of a thumb-push cap for rigidly holding one end of the pressure absorbing device in position, and a receiving means provided in the cap cavity for receiving and supporting another end of the pressure absorbing device in position. Therefore the pressure absorbing device is vertically held between the thumb-push cap and the ceiling of the casing for urging the thumb-push cap at an upper normal position thereof and providing an additional press resistance to the thumb-push cap, so as to resist a downwardly press force applied by an under age child on the thumb-push cap while an adult is capable of pushing down the thumb-push cap easily.

## 6 Claims, 4 Drawing Sheets

